

AIR COOLED PETROL ENGINES**SINGLE CYLINDER****Features :**

- | Air cooled, Four stroke, OHV, Single cylinder engine
- | Efficient air filter system
- | Compact and light weight
- | Both Recoil & Electric start models available
- | Easy to start, Smooth running & Low vibration

Specifications

MODEL	PE-160		PE-200		PE-210		PE-270		PE-390		PE-420	
Engine Speed rpm	3000	3600	3000	3600	3000	3600	3000	3600	3000	3600	3000	3600
Rated Output HP	4.3		5.0		5.5		7.2		10.0		11.0	
Max. Output HP	5.5		6.5		7.0		9.0		13.0		16.0	
Max. Torque	10/2500		11/2500		12/2500		16.5/2500		22.5/2500		24.5/2500	
Displacement cc	163		196		208		270		389		420	
Bore x Stroke mm	68 x 45		68 x 54		70 x 54		77 x 58		88 x 64		90 x 66	
Fuel Tank Capacity L	3.6		3.6		3.6		6		6		6	
Lube Oil Capacity L	0.6		0.6		0.6		1.1		1.4		1.4	
Fuel Consumption (g/hp.hr)	294		294		294		278		278		276	
Dimension (l x b x h) mm	315 x 362 x 335		315 x 362 x 335		315 x 362 x 335		380 x 430 x 410		490 x 460 x 520		490 x 460 x 520	
Net Weight kg	14		16		16		25		31		31	

Optional : All above models are available with electric start system (Suffix letter "E" for Electric start models)

DOUBLE CYLINDER**Specifications**

MODEL	PE-620	
Engine Speed rpm	3000	3600
Rated Output HP	17.0	
Max. Output HP	20.0	
Max. Torque	38.5/2500	
Displacement cc	614	
Bore x Stroke mm	77 x 66	
Fuel Tank Capacity L	7	
Lube Oil Capacity L	1.5	
Fuel Consumption (g/hp.hr)	276	
Dimension (l x b x h) mm	390 x 460 x 455	
Net Weight kg	43	

In view of continuous development, the information / descriptions / specifications / illustrations are subject to change without notice.